

Upanel1.4S

Intelligent Front Access

16:9 LED Display Unit



Main Technical Specifications:

Parameter	Value
Pixel Pitch	1.46mm
LED Type	SMD
LED Configuration	1Red,1Green,1Blue
Brightness	600cd/m ²
Pixels Per Panel	416×234 Dots
Pixel Density	465,299 pixels/m ²
Weight	7.5 kg/panel
Module Size	W304.96mm×H343.08mm
Cabinet Size	W609.92mm×H343.08mm×D71mm
Cabinet Diagonal	27.5"(699.79mm)
Aspect Ratio	16:9
Area	0.209 m ²
Recommended Viewing Distance	≥1.4 m
Material	Die-casting Aluminum
Environment	Indoor
Ingress Protection	IP50
Operating Temperature/Humidity	-10°C~+45°C/10~80%RH
Storage Temperature/Humidity	-20°C~+55°C/10~85%RH
Maintenance	Intelligent Front Service
Gap Between Modules	Seamless

Horizontal Viewing Angle	+/-80°
Vertical Viewing Angle	+/-80°
Color Temperature	2000-9500K Adjustable
Colors	4.4 Trillion
Brightness Control	Manual/Automatic
Contrast Ratio	5000:1
Input Power <Max>	120W/ panel
Input Power <Typical>	40W /panel
Driving Method	Constant Current Drive
Video Frame Rate	50/60 Hz
Rate Refresh	1920 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video, etc
Calibration	Support brightness and chroma
Acoustic Noise	Fanless operation
LED Life Time	≥100,000 Hours
Standard Mounting Configuration	Stacking
Optional Mounting Configuration	Floor-mounted, corner mounted via back frame
Video Signal Redundancy	Optional
Video Extension Redundancy	Optional
Professional Services	Design, configuration, install and service available
Data Interconnection	CAT5 Cable; multi-mode fiber; single mode fiber

Note: Specifications are subjected to change without notice.

